



ATRIA FW

SPECIFICATIONS

base code	66129
typology	Wall mounting glare free floorwasher with trim
mounting	In concrete using housing box (code: 69397 or 69398) to be separately ordered as accessory
diameter	103 mm / 4.1"
height	83 mm / 3.3"
required depth	Depending on housing box
first fit requirement	Yes, separate housing box: code 69397 or code 69398 (adjustable height)
surface cut out	100 mm / 3.94"
construction	Fixture and flange: turning and milling aluminum. Reflector: polycarbonate Protective glass or PMMA complete with silicone gasket. Housing box: PVC
finishes	Powder coated
ingress protection	IP66. North America wet location
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	8W at 48V DC. North America: 8W at 24V DC
lamp lumens	720lm
delivered lumens	530lm
lumen maintenance	50.000h L90
beam	Asymmetrical: 5° - 75° towards the floor
kelvin	2200K CRI80, 2200K CRI90, 2700K CRI93, 3000K CRI93 and 4000K CRI93 / 3 step MacAdam ellipse
special features	48V DC: unpolarized electronic system. 24V DC: reverse polarity protection. Thermal Sensor. Safe wiring. Two wires dimming. Thanks to the design of the reflector, the luminaire is totally glare free and delivers homogenous light from the lower edge of the wall with no visible dark zones
dimming options	Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL listed for wet location





EXCELLENT HORIZONTAL UNIFORMITY:
LIGHT IS CONVEYED PRECISELY TOWARDS THE FLOOR
FROM THE LOWER EDGE OF THE WALL


ATRIA FW

INSTALLATION GUIDE

FOR A GOOD UNIFORMITY OF LIGHT ON THE FLOOR, FOLLOW THESE RULES:


1

The **distance from the floor D** shall be $L / 5$




2

The **spacing between luminaires S** shall be the $D \times 0,8$



Example


L	3 m / 9' 10"	D	$L / 5 = 0,6 \text{ m} / 24"$
		S	$D \times 0,8 = 0,5 \text{ m} / 20"$



20lx 50lx 100lx 200lx

FLOORWASHER OPTIONS

AVAILABLE OPTIONS FOR DIFFERENT FLOOR DEPTHS



DOT 30 FW
1W, 25lm delivered

SEE PAGE 483

