



# B RING LARGE

## SPECIFICATIONS

year	2016
project	Private residence, Moscow - Russia
typology	<b>Eighteen different pendant luminaires</b> , with light emission <b>on two sides (direct light and indirect light)</b>
mounting	To ceiling with 3000 mm steel wire ropes
diameter	1000 / 39.37" - 1500 / 59.06" - 2000 mm / 78.74" - 2500 mm / 98.43" - <b>4000 mm / 157.48"</b>
height	160 mm / 6.30"
width	90 mm / 3.54"
construction	Extruded aluminum fixture. Diffuser in polycarbonate
finishes	<b>Polished chrome, powder coated when painted, leather, silver leaf</b>
ingress protection	IP20
lamp quantity	2
lamp type	LED array on printed circuit board. Remote power supply
lamp wattage	B RING 100: 195W / B RING 150: 320W / B RING 200: 425W / B RING 250: 530W / B RING 400: 845W at 48V DC
special features	Diffuse and completely homogenous light distribution across the entire surface. <b>DALI dimmable</b>
colour temperatures	3000K CRI93
lamp lumens	From 20.000lm to 43.000lm
lamp efficacy lm/W	101lm/W
lumen maintenance	50.000hrs lifetime with lumen maintenance at L70
dimming options	DALI
certifications	CE



