



# BUTTON DO

## SPECIFICATIONS

base code	BUTTON 60 DO: 67932 - BUTTON 100 DO: 67933 - BUTTON 200 DO: 67935
typology	In-ground round luminaire with a drive over load of 2,5 tonnes / 5500 lbs
mounting	Using housing box to be separately ordered as accessory
diameter	BUTTON 60 DO: 55 mm / 2.2" - BUTTON 100 DO: 95 mm / 3.7" BUTTON 200 DO: 193 mm / 7.6"
height	70 mm / 2.8"
required depth	Depending on housing box
first fit requirement	Yes, separate housing box. Millimetric height adjustment from 0 to 50 mm / from 0" to 2": BUTTON 60 DO: code 69427 or 69424 (adjustable height) BUTTON 100 DO: code 69443 or 69445 (adjustable height) BUTTON 200 DO: code 69423 or 69426 (adjustable height)
floor cut out	Depending on housing box
construction	Fixture: turning and milling aluminum. Tempered glass diffuser - 15 mm / 0.6" thickness - complete with silicone gasket. Housing box in PVC
finishes	Fixture anodized. Glass surface
ingress protection	IP67. North America: wet location. Built-in protection from water infiltration and moisture
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	BUTTON 60 DO: 1,5W at 24V DC. BUTTON 100 DO: 1,5W at 24V DC. BUTTON 200 DO: 6W at 24V DC
delivered lumens	1,5W: 80lm. 6W: 300lm
lumen maintenance	50.000h L90
beam	Diffused
kelvin	2200K CRI90 (BUTTON 60 / 100 DO only), 2700K CRI93, 3000K CRI93, 4100K CRI93 / 3 step MacAdam ellipse
special features	Unpolarized Electronic System. Safe Wiring. Two Wires Dimming. Water Stop Technology. Diffuse and completely homogenous light distribution across the entire surface
control protocols	0-10V, DMX or DALI
certifications	CE, ETL listed (certified to UL 2108, CSA C22.2)



DIFFUSE AND COMPLETELY HOMOGENOUS  
LIGHT DISTRIBUTION ACROSS THE ENTIRE SURFACE






# BUTTON DO

## ORDER CODE

### BASE CODE

- 67932** BUTTON 60 DO
- 67933** BUTTON 100 DO
- 67935** BUTTON 200 DO

### A . POWER SUPPLY

- 9** 24V DC power supply NOT included
- R**  listed 24V DC power supply NOT included

### B . KELVIN

- 4** 4100K CRI93
- 5** 3000K CRI93
- 8** 2700K CRI93
- D** 2200K CRI90 *BUTTON 60 / 100 DO ONLY*

### C . DIFFUSER

- 9** frosted

Example: BASE CODE **67932** A **9** B **8** C **9** D **G** = **67932-989G**

### D . FINISHES

- G** glass



## ACCESSORIES

### REQUIRED ACCESSORIES - NOT INCLUDED

code	description	dimensions mm
69427	housing box for concrete	Ø60xH110
69424	height adjustable housing box for concrete	Ø150xH114-164
69443	housing box for concrete	Ø100xH100
69445	height adjustable housing box for concrete	Ø150xH106-156
69423	housing box for concrete	Ø200xH100
69426	height adjustable housing box for concrete	Ø240xH102-152
69592	suction cup for BUTTON 60 DO	W50xH40
69593	suction cup for BUTTON 100 / 200 DO	W80xH50





# BUTTON DO

## ACCESSORIES

### REQUIRED ACCESSORIES - NOT INCLUDED

Power supply  
24V DC\*, ON/OFF  
ambient temperature up to 60° C

code	output power	input voltage / frequency	IP	dimensions mm
69061	40W	90-305V 47-63Hz	IP67	L171xW62xH37
69062	60W	90-305V 50-60Hz	IP67	L171xW62xH37
69063	100W	90-305V 50-60Hz	IP67	L220xW68xH39

Power supply  
24V DC\*, DALI


69220	120W	90-305V 47-63Hz	IP65	L191xW63xH38
-------	------	-----------------	------	--------------

Power supply  
24V DC\*, 0-10V

69215	60W	90-305V 47-63Hz	IP65	L150xW53xH35
-------	-----	-----------------	------	--------------

Class 2 power supply  
24V DC\*

Consult **B LIGHT North America**  
Lighting Group Network  
T: 212.775.6363  
E: info@lightinggroupnetwork.com



code	description	dimensions mm
69842	IP68 connector, 1 IN - 1 OUT, 2 wires	W37xD22xH37
69847	IP68 connector, 1 IN - 3 OUT, parallel wiring, 2 wires for BUTTON 100 DO / BUTTON 200 DO	W45xD30xH17