

DOT 45


SPECIFICATIONS



base code	64050
typology	Glare free compact downlight with symmetrical or asymmetrical (wallwasher and downlight) light distribution
mounting	In plasterboard using springs (included)
diameter	45 mm / 1.77"
height	32 mm / 1.26"
required depth	25 mm / 0.98"
ceiling cut out	40 mm / 1.57"
construction	Fixture and flange: turning and milling aluminum. Reflector: polycarbonate complete with silicone gasket
finishes	Powder coated. Heat sink anodized
ingress protection	IP30
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	3W at 24V DC
lamp lumens	330lm
delivered lumens	240lm
lumen maintenance	50.000h L90
beam	40°
kelvin	2700K CRI93, 3000K CRI93 or 4000K CRI93
special features	Protection against wrong connections - Two wires dimming. Designed with symmetrical and asymmetrical reflectors, delivers glare free homogeneous light. The asymmetrical reflector offers longitudinal cut-off and delivers homogeneous light from the upper edge of the wall to the floor with no visible dark zones
dimming options	Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
standards	CE




SYMMETRICAL REFLECTOR



ASYMMETRICAL REFLECTOR: 25° AND WALLWASHER

SYMMETRICAL

Ø 45



ASYMMETRICAL

Ø 45



25 mm
0.98"

40 mm
1.57"

0.05 kg
0.11 lbs



DOT 45

ORDER CODE

BASE CODE

64050

A . POWER SUPPLY

2 24V DC
EXCL. power
supply

B . KELVIN

4 4000K CRI93
5 3000K CRI93
8 2700K CRI93

C . DIFFUSER

5 wide flood 40°
A asymmetrical

Example: BASE CODE 64050 A B C D
2 5 5 2 = 64050-2552

D . FINISHES

6 white
RAL 9006



2 black
RAL 9002



5 polished
stainless steel

