

DOT IN LINE





SPECIFICATIONS

base code	64056
typology	Glare free compact downlight with a small aperture
mounting	On surface
length	50 mm / 1.97"
width	70 mm / 2.76"
height	32 mm / 1.26"
required depth	35 mm / 1.37"
construction	Fixture and flange: turning and milling aluminum. Lens: PMMA. Cap: polycarbonate
finishes	Powder coated. Heat sink anodized
ingress protection	IP40
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	6W at 24V DC
lamp lumens	600lm
delivered lumens	480lm
lumen maintenance	50.000h L90
beam	40°
kelvin	2700K CRI93, 3000K CRI93 or 4000K CRI93 / 3 step MacAdam ellipse
special features	Protection against wrong connections - Two wires dimming. Designed with innovative lens technology, delivers glare free light.
dimming options	Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
standards	CE



VISIBLE APERTURE

Ø 13





DOT IN LINE

ORDER CODE

BASE CODE

64056

A . POWER SUPPLY

2 24V DC
EXCL. power
supply

B . KELVIN

4 4000K CRI93
5 3000K CRI93
8 2700K CRI93

C . DIFFUSER

5 wide flood 40°

Example: BASE CODE A B C D
64056 2 5 5 2 = 64056-2552

D . FINISHES

2 black 