





GARDEN RAZOR NEW



SPECIFICATIONS

base code	672
typology	Linear garden luminaire with light distribution on one side
mounting	On ground with stem. Cable length 2000 mm / 78.7"
height	1030 mm / 40.6" or 1630 mm / 64.2"
diameter	End cap: 15 mm / 0.6". Stem: 6 mm / 0.2"
construction	End cap: turning and milling aluminum. Fixture: Flexible stem in composite carbon fiberglass. Lower section: stainless steel AISI 304
finishes	Marine grade powder coated (head)
ingress protection	IP66. North America wet location
lamp type	Linear LED array on printed circuit board. Height 1030mm: PCB L 500 mm / 19.6". Height 1630mm: PCB L 1000 mm / 39.2". Remote power supply not included
lamp wattage	Height 1030 mm: 3W at 48V DC. North America 24V DC Height 1630 mm: 6W at 48V DC. North America 24V DC
lamp lumens	100lm/W
delivered lumens	50lm/W
lumen maintenance	50.000h L90
beam	Diffused
kelvin	2000K CRI93, 2700K CRI93 or 3300K CRI93 / 3 step MacAdam ellipse
special features	Reverse polarity protection - Two wires dimming
dimming options	Push button, potentiometer, 0-10V, DALI. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL approval pending



* weight referred to the 1000 mm / 39.4" model

GARDEN RAZOR

ORDER CODE

BASE CODE	A1. STEM LENGTH	A. POWER SUPPLY	B. KELVIN	C. DIFFUSER
672	43 1030 mm 45 1630 mm	8 48V DC power supply NOT included R listed 24V DC power supply NOT included	5 3300K CRI93 8 2700K CRI93 D 2000K CRI93	1 frosted

Example: BASE CODE **672** A1 **43** A **8** B **8** C **1** D **2** = **67243-8812**

D. FINISHES

2 black
RAL 9005



ACCESSORIES

REQUIRED ACCESSORIES - NOT INCLUDED

	code	output power	input voltage / frequency	IP	dimensions mm
Power supply 48V DC*, ON/OFF	69180	30W	90-264V 47-63Hz	IP20	L160xW46xH30
Power supply 48V DC, 1-10V ¹ or ON/OFF* ambient temperature up to 60° C	69185	40W	90-305V 47-63Hz	IP67	L171xW62xH37
Power supply 48V DC*, DALI ¹ ambient temperature up to 60° C	69195	75W	100-305V 47-63Hz	IP67	L180xW63xH36
Power supply 48V DC, 1-10V and DALI	69096	55W	99-264V 50-60Hz	IP20	L129xW76xH30
Class 2 power supply 24V DC					

¹for a perfect dimming, it is necessary that the power supply is saturated to 100%

Consult **B LIGHT North America**
Lighting Group Network
T: 212.775.6363
E: info@lightinggroupnetwork.com




code	description	dimensions mm
69842	IP68 connector, 1 IN - 1 OUT, 2 wires	W37xD22xH37
69847	IP68 connector, 1 IN - 2 OUT, parallel wiring, 2 wires	W45xD30xH17

OPTIONAL ACCESSORIES



code	description	dimensions mm
69864	stainless steel AISI 304 spike	Ø42xH200

The luminaire offers a **longitudinal cut-off** delivering glare free homogeneous light



CONTINUOUS MOVEMENT WITH BREEZE

