




GARDEN RAZOR

SPECIFICATIONS

base code	67243 - 67245
typology	Linear garden luminaire with light distribution on one side
mounting	On ground with stem. Cable length 2000 mm / 78.7"
height	1030 mm / 40.6" or 1630 mm / 64.2"
diameter	End cap: 15 mm / 0.6". Stem: 6 mm / 0.2"
construction	End cap: turning and milling aluminum. Fixture: Flexible stem in composite carbon fiberglass. Lower section: stainless steel AISI 304
finishes	Marine grade powder coated (end cap)
ingress protection	IP66. North America: wet location
lamp type	Linear LED array on printed circuit board. Height 1030mm: PCB L 500 mm / 19.6". Height 1630mm: PCB L 1000 mm / 39.2". Remote power supply not included
lamp wattage	Height 1030 mm: 3W at 24V DC. Height 1630 mm: 6W at 24V DC
delivered lumens	3W: 30lm. 6W: 60lm
lumen maintenance	50.000h L90
beam	Diffused
kelvin	2200K CRI93, 2700K CRI93 or 3000K CRI93 / 3 step MacAdam ellipse
special features	Reverse Polarity Protection. Water Stop Technology. Two Wires Dimming
control protocols	0-10V, DMX or DALI
certifications	CE, ETL listed (certified to UL 2108, CSA C22.2)



0.2 kg *
1.1 lbs *

* weight referred to the 1000 mm / 39.4" model




GARDEN RAZOR

ORDER CODE

BASE CODE	A1 . STEM HEIGHT	A . POWER SUPPLY	B . KELVIN	C . DIFFUSER
672	43 1030 mm 45 1630 mm	9 24V DC power supply NOT included R  listed 24V DC power supply NOT included	5 3000K CRI93 8 2700K CRI93 D 2200K CRI93	1 frosted
Example: BASE CODE 672 A1 43 A 9 B 8 C 1 D 2 = 67243-9812				
D . FINISHES				
2	black RAL 9005			

ACCESSORIES

REQUIRED ACCESSORIES - NOT INCLUDED

	code	output power	input voltage / frequency		IP	dimensions mm
Power supply 24V DC*, ON/OFF ambient temperature up to 60° C	69061	40W	90-305V	47-63Hz	IP67	L171xW62xH37
	69062	60W	90-305V	50-60Hz	IP67	L171xW62xH37
	69063	100W	90-305V	50-60Hz	IP67	L220xW68xH39
Power supply 24V DC*, DALI	69220	120W	90-305V	47-63Hz	IP65	L191xW63xH38
Power supply 24V DC*, 0-10V	69215	60W	90-305V	47-63Hz	IP65	L150xW53xH35
Class 2 power supply 24V DC* 	Consult B LIGHT North America Lighting Group Network T: 212.775.6363 E: info@lightinggroupnetwork.com					
	code	description				dimensions mm
	69842	IP68 connector, 1 IN - 1 OUT, 2 wires				W37xD22xH37
	69847	IP68 connector, 1 IN - 3 OUT, parallel wiring, 2 wires				W45xD30xH17

OPTIONAL ACCESSORIES

	code	description	dimensions mm
	69864	stainless steel AISI 304 spike	Ø42xH270

The luminaire offers a **longitudinal cut-off** delivering glare free homogeneous light



- 2lx
- 4lx
- 8lx
- 16lx