





INSERTO MEDIUM 65 SD

SPECIFICATIONS


base code	649
typology	Linear pendant luminaire
mounting	To ceiling with 2000 mm / 78.74" steel wire ropes (included)
length	Available in eight lengths, from 780 to 2530 mm / from 30.71" to 99.61"
height	65 mm / 2.56"
width	40 mm / 1.57"
construction	Extruded aluminum fixture. End caps in turning and milling aluminum. Diffuser in polycarbonate
finishes	Anodized or powder coated when painted
ingress protection	IP40. North America dry location
lamp type	Linear LED array on printed circuit board. PCB L 250 mm / 9.84". PCB increment 250 mm / 9.84" - 2500 mm / 98.43" max. Custom dimensions on request. Remote power supply not included
LED pitch	4,1 mm / 0.16" (480 LEDs per meter)
lamp wattage	From 9W to 100W at 48V DC (RGB at 24V DC). North America 24V DC
lamp lumens	PCB L 250: 2700K CRI93 - 830lm, 3000K CRI93 - 830lm, 4000K CRI93 - 915lm
delivered lumens	PCB L 250: 415lm (3000K CRI93, satin) - 600lm (3000K CRI93, microprismatic)
lumen maintenance	50.000h L90
beam	Diffused or microprismatic
kelvin	2700K CRI93, 3000K CRI93, 4000K CRI93 and RGB / 3 step MacAdam ellipse
special features	Unpolarized electronic system (reverse polarity protection for RGB) - Two wires dimming. Diffuse and completely homogenous light distribution across the entire surface
dimming options	Push button, potentiometer, remote control, 1-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL listed for dry location



* weight based on 250 mm / 9.84"

INSERTO MEDIUM 65 SD





ORDER CODE

BASE CODE	A1 . LENGTH			A . POWER SUPPLY		B . KELVIN		
		white	RGB					
649	03	780 mm	30 W	9 W	8	48V DC EXCL. power supply	4	4000K CRI93
	04	1030 mm	40 W	12 W	2	24V DC EXCL. power supply RGB only	5	3000K CRI93
	05	1280 mm	50 W	15 W	R  listed 24V DC EXCL. power supply	6	RGB ¹	
	06	1530 mm	60 W	18 W		8	2700K CRI93	
	07	1780 mm	70 W	21 W				
	08	2030 mm	80 W	24 W				
	09	2280 mm	90 W	27 W				
	10	2530 mm	100 W	30 W				

¹ flush diffuser in satin white only

Example: BASE CODE A1 A B C D
649 03 8 5 A 6 = 64903-85A6

C . DIFFUSER

- A** satin flush diffuser 
- B** microprismatic flush diffuser 
- C** satin recessed diffuser 
- D** microprismatic recessed diffuser 

D . FINISHES

- 1** grey anodized 
- 6** white RAL 9003 
- D** black anodized 

INSERTO MEDIUM 65 SD

ACCESSORIES


REQUIRED ACCESSORIES - NOT INCLUDED

code	output power	input voltage / frequency	IP	dimensions mm
69181	40W	90-305V	47-63Hz IP67	L163xW43xH32
69182	60W	90-305V	47-63Hz IP67	L163xW43xH32
69183	100W	90-264V	47-63Hz IP20	L201xW70xH35
69188	150W	90-305V	47-63Hz IP67	L228xW68xH39
69189	240W	90-305V	47-63Hz IP67	L244xW68xH39
69185	40W	90-305V	47-63Hz IP67	L171xW62xH37
69186	60W	90-305V	47-63Hz IP67	L171xW62xH37
69187	100W	90-305V	47-63Hz IP67	L220xW68xH39
69188	150W	90-305V	47-63Hz IP67	L228xW68xH39
69189	240W	90-305V	47-63Hz IP67	L244xW68xH39
69195	75W	100-305V	47-63Hz IP67	L180xW63xH36
69196	100W	100-305V	47-63Hz IP67	L199xW63xH36
69197	150W	100-305V	47-63Hz IP67	L219xW63xH36

RGB requires 24V DC:
Please see INSERTO MINI CL (pag. 277) for drivers list

Class 2 power supply 24V DC

Consult **B LIGHT North America**
Lighting Group Network
T: 212.775.6363
E: info@lightinggroupnetwork.com



Control unit 24V DC - 48V DC RGB interface²⁾

code	page	description	in/out voltage	IP	dimensions mm
69144	582	SMART RGB MASTER 2 RGB interface master (max load 240W at 24V DC or 320W at 48V DC and No. 32 SMART RGB SLAVE 2)	24V DC - 48V DC	IP20	W116xD116xH25
69145	582	SMART RGB SLAVE 2 DMX interface or RGB interface slave (max load 240W at 24V DC or 320W at 48V DC)	24V DC - 48V DC	IP20	W116xD116xH25

²⁾ Inserto Medium 65 SD RGB works only with B LIGHT's RGB interface. It is not possible to order the luminaire separately from the RGB interface

OPTIONAL ACCESSORIES

code	description	dimensions mm
69161	RGB remote control	W85xD50xH7