





KUBO 54 W2

KUBO 54 W / KUBO 54 W2

SPECIFICATIONS

base code	66415 KUBO 54 W - 66416 KUBO 54 W2
typology	Wall mounting luminaire with light emission on one side (KUBO 54 W) or two sides, direct light and indirect light (KUBO 54 W2)
mounting	On wall using mounting plate
width	54 mm / 2.1"
depth	KUBO 54 W: 54 mm / 2.1" KUBO 54 W2: 62 mm / 2.4"
height	KUBO 54 W: 54 mm / 2.1" KUBO 54 W2: 110 mm / 4.3"
construction	Fixture: turning and milling aluminum. Lens: PMMA. Protective glass in PMMA complete with silicone gasket
finishes	Powder coated
ingress protection	IP67. North America wet location. Built-in protection from water infiltration and moisture
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	KUBO 54 W: 5W at 48V DC and 350 mA. North America 24V DC and 350 mA. KUBO 54 W2: 10W (5W direct light and 5W indirect light) at 48V DC and 350 mA. North America 24V DC and 350 mA
lamp lumens	KUBO 54 W: 420lm - KUBO 54 W2: 840lm
delivered lumens	KUBO 54 W: 270lm (3000K CRI93, 36°) - KUBO 54 W2: 540lm (3000K CRI93, 36°)
lumen maintenance	50.000h L90
beam	16°, 36°, 45°
kelvin	2200K CRI80, 2200K CRI93, 2700K CRI93, 3000K CRI93 / 3 step MacAdam ellipse
special features	Unpolarized electronic system (24V DC: reverse polarity protection). Safe wiring. 48V DC, 24V DC: Thermal Sensor. Two wires dimming. Water stop technology
dimming options	Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL listed for wet location



KUBO 54 W / KUBO 54 W2

ORDER CODE

BASE CODE	A . POWER SUPPLY	B . KELVIN	C . BEAM
66415 KUBO 54 W	8 48V DC power supply NOT included	5 3000K CRI93	2 spot 16°
66416 KUBO 54 W2	L 350 mA power supply NOT included	8 2700K CRI93	4 flood 36°
	R  listed 24V DC power supply NOT included	D 2200K CRI93 (350 mA)	5 wide flood 45°
	U  listed 350 mA power supply NOT included	I 2200K CRI80 (24/48V DC)	
Example: BASE CODE A B C D 66415 8 8 4 6 = 66415-8846			
D . FINISHES			
6 white RAL 9003		F golden bronze	
Q anthracite RAL 7024			

KUBO 54 W / KUBO 54 W2

ACCESSORIES

REQUIRED ACCESSORIES - NOT INCLUDED					
	code	output power	input voltage / frequency	IP	dimensions mm
Power supply 48V DC, ON/OFF*	69181	40W	90-305V	47-63Hz	IP54 L163xW43xH32
	69182	60W	90-305V	47-63Hz	IP54 L163xW43xH32
Power supply 48V DC, 1-10V [®] or ON/OFF* ambient temperature up to 60° C	69185	40W	90-305V	47-63Hz	IP67 L171xW62xH37
	69186	60W	90-305V	47-63Hz	IP67 L171xW62xH37
Power supply 48V DC, DALI [®] ambient temperature up to 60° C	69195	75W	100-305V	47-63Hz	IP67 L180xW63xH36
	¹for a perfect dimming, it is necessary that the power supply is saturated to 100%				
Power supply 48V DC, 1-10V and DALI	69096	55W	99-264V	50-60Hz	IP20 L129xW76xH30
	69097	120W	90-305V	47-63Hz	IP67 L191xW63xH38
Power supply 350 mA max No. fixtures KUBO 54 W only	69086	ON/OFF, 15W / max 3	90-264V	50-60Hz	IP20 L115xW34XH19
	69090	1-10V, 18W / max 3	99-264V	50-60Hz	IP20 L120xW52XH22
	69079	DALI, 15W / max 3	110-240V	50-60Hz	IP20 L120xW52xH22
	69205	DALI, 17W / max 3	99-264V	50-60Hz	IP67 L122xW54xH26
Power supply 350 mA max No. fixtures KUBO 54 W2 only	69086	ON/OFF, 15W / max 1	90-264V	50-60Hz	IP20 L115xW34XH19
	69090	1-10V, 18W / max 2	99-264V	50-60Hz	IP20 L120xW52XH22
	69079	DALI, 15W / max 1	110-240V	50-60Hz	IP20 L120xW52xH22
	69205	DALI, 17W / max 1	99-264V	50-60Hz	IP67 L122xW54xH26
Class 2 power supply 24V DC 350 mA  listed	Consult B LIGHT North America Lighting Group Network T: 212.775.6363 E: info@lightinggroupnetwork.com				



KUBO 54 W

*To choose the power supply, always add a spare 20% as safety margin.
See pag 509 for cable size and max wiring distance from power supply to last connected luminaire