




MAIA X1

SPECIFICATIONS

base code	672
typology	Projector with recessed antiglare optics
mounting	On surface by fixing base or on ground using stainless steel AISI 304 spike (code 69857) to be separately ordered as accessory
stem height	190 - 350 - 700 mm / 7.5"- 13.8"- 27.6"
diameter	89 mm / 3.5"
length	142 mm / 5.6"
construction	Fixture: turning and milling aluminum. Stainless steel A2 screws. Reflector: polycarbonate. Protective glass complete with silicone gasket
finishes	Powder coated
ingress protection	IP66. North America wet location. Built-in protection from water infiltration and moisture
lamp type	COB. Remote power supply not included
lamp wattage	16W at 48V DC and 500 mA. North America 500 mA
lamp lumens	2700K CRI93 - 1780lm, 3000K CRI93 - 1840lm, 4000K CRI93 - 1970lm
delivered lumens	1300lm (3000K CRI93, 36°)
lumen maintenance	50.000h L80
beam	15°, 36°, 51°. Adjustable 330° on the vertical plane
kelvin	2700K CRI93, 3000K CRI93 and 4000K CRI93 / 3 step MacAdam ellipse
special features	Water drainage system - Water stop technology. 48V DC: unpolarized electronic system - Thermal Sensor - Safe wiring
dimming options	Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL listed for wet location



* weight referred to the 190 mm / 7.48" model

MAIA X1

ORDER CODE



BASE CODE	A1 . STEM HEIGHT	A . POWER SUPPLY	B . KELVIN	C . BEAM
672	17 190 mm 18 350 mm 19 700 mm	8 48V DC power supply NOT included L 500 mA power supply NOT included U  listed 500 mA power supply NOT included	4 4000K CRI93 5 3000K CRI93 8 2700K CRI93	2 spot 15° 4 flood 36° 5 wide flood 51°
Example: BASE CODE A1 A B C D E 672 17 8 8 4 6 A = 67217-8846A				
D . FINISHES			E . OTHER	
F golden bronze			A hidden cable exit	
Q anthracite RAL 7024			B side cable exit	
A grey RAL 9006				



MAIA X1

ACCESSORIES

REQUIRED ACCESSORIES - NOT INCLUDED

	code	output power	input voltage / frequency	IP	dimensions mm
Power supply 48V DC* ON/OFF	69180	30W	90-264V	47-63Hz IP20	L160xW46xH30
Power supply 48V DC* ON/OFF	69185	40W	90-305V	47-63Hz IP67	L171xW62xH37
for ambient temperature up to 60° C	69186	60W	90-305V	47-63Hz IP67	L171xW62xH37
	69187	100W	90-305V	47-63Hz IP67	L220xW68xH39
Power supply 48V DC* DALI®	69195	75W	100-305V	47-63Hz IP67	L180xW63xH36
for ambient temperature up to 60° C	69196	100W	100-305V	47-63Hz IP67	L199xW63xH36
	*on / off only				
Power supply 500 mA max No. fixtures	69088	ON/OFF, 20W / max 1	100-264V	50-60Hz IP20	L135xW38xH28
	69091	1-10V, 20W / max 1	99-264V	50-60Hz IP20	L120xW52xH22
	69080	DALI, 20W / max 1	220-240V	50-60Hz IP20	L120xW52xH22
	69206	DALI, 24W / max 1	99-264V	50-60Hz IP67	L122xW54xH26
Class 2 power supply 500 mA	Consult B LIGHT North America Lighting Group Network T: 212.775.6363 E: info@lightinggroupnetwork.com				
	code	description			dimensions mm
	69841	IP68 connector, 1 IN - 1 OUT, 3 wires			W42xD29xH42
	69843	IP68 connector, 1 IN - 3 OUT, parallel wiring, 4 wires			W78xD30xH20

OPTIONAL ACCESSORIES

	code	description	dimensions mm
	69862	spike	W60xD30xH240
	69877-6	half snoot for glare control - white RAL 9003	Ø91xH138
	69877-A	half snoot for glare control - grey RAL 9006	Ø91xH138
	69877-F	half snoot for glare control - golden bronze	Ø91xH138
	69877-Q	half snoot for glare control - anthracite RAL 7024	Ø91xH138

SPECIAL FEATURE: WATER DRAINAGE SYSTEM



When aimed upwards, the water is collected in the cup and is drained from the bezel cavities

