



# MINI TONDO



## SPECIFICATIONS

base code	672
typology	Garden or pathway luminaire
mounting	On ground with stem. Cable length 2000 mm / 78.7"
stem height	635 mm / 25" or 1035 / 40.7"
diameter	35 mm / 1.4"
construction	Fixture: turning and milling aluminium. Flexible stem in composite fiberglass
finishes	Marine grade powder coated (head)
ingress protection	IP65. North America wet location
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	1W at 48V DC. North America 24V DC
lamp lumens	200lm
delivered lumens	100lm
lumen maintenance	50.000h L90
beam	Diffused
kelvin	2000K CRI93, 2700K CRI93 or 3300K CRI93 / 3 step MacAdam ellipse
special features	Thanks to the shielded light, the luminaire is glare free and compliant with the rules against light pollution. Unpolarized electronic system. Two wires dimming
dimming options	Push button, potentiometer, 0-10V, DALI. Dimming options depend on power supply and additional control units to be separately ordered as accessories
listings	CE, ETL approval pending

Ø 35 / 1.4"



13 / 0.5"



315 / 12.4"


635 / 25" - 1035 / 40.7"



0.2 kg  
0.4 lbs


# MINI TONDO

## ORDER CODE

BASE CODE	A1 . STEM HEIGHT	A . POWER SUPPLY	B . KELVIN	C . DIFFUSER
<b>672</b>	<b>47</b> 635 mm <b>49</b> 1035 mm	<b>8</b> 48V DC power supply NOT included <b>R</b>  listed 24V DC power supply NOT included	<b>5</b> 3300K CR193 <b>8</b> 2700K CR193 <b>D</b> 2000K CR193	<b>1</b> frosted

Example: BASE CODE **672** A1 **47** A **8** B **8** C **1** D **F** = **67247-881F**

## D . FINISHES

**F** golden bronze 

## ACCESSORIES

### REQUIRED ACCESSORIES - NOT INCLUDED

code	output power	input voltage / frequency	IP	dimensions mm
69180	30W	90-264V 47-63Hz	IP20	L160xW46xH30
69185	40W	90-305V 47-63Hz	IP67	L171xW62xH37
69195	75W	100-305V 47-63Hz	IP67	L180xW63xH36
69096	55W	99-264V 50-60Hz	IP20	L129xW76xH30

\*for a perfect dimming, it is necessary that the power supply is saturated to 100%

Class 2 power supply 24V DC  
Consult **B LIGHT North America**  
Lighting Group Network  
T: 212.775.6363  
E: info@lightinggroupnetwork.com

code	description	dimensions mm
69842	IP68 connector, 1 IN - 1 OUT, 2 wires	W37xD22xH37
69847	IP68 connector, 1 IN - 2 OUT, parallel wiring, 2 wires	W45xD30xH17

### OPTIONAL ACCESSORIES

code	description	dimensions mm
69864	stainless steel AISI 304 spike	Ø42xH200

\*To choose the power supply, always add a spare 20% as safety margin.  
See pag 495 for cable size and max wiring distance from power supply to last connected luminaire