


# OKKIO 35 T

## SPECIFICATIONS

code	SS007-2552A
typology	Ceiling recessed luminaire
mounting	To ceiling using springs (included)
diameter	42 mm / 1.7"
height	52 mm / 2.1"
required depth	55 mm / 2.2"
ceiling cut-out	37 mm / 1.46"
construction	Fixture: turning and milling aluminum. Lens: PMMA
finishes	Black anodized
ingress protection	IP40 or IP65
lamp type	LED array on printed circuit board. Remote power supply not included
lamp wattage	4,5W at 24V DC. Red light: 3W at 24V DC
lamp lumens	400lm
delivered lumens	330lm
lumen maintenance	50.000h L90
beam	15°, 34°, 40°
kelvin	Red, 2700K CRI93, 3000K CRI93 and 4000K CRI93 / 2 step MacAdam ellipse
special features	Red light for navigation. Protection against wrong connections - Two wires dimming
dimming options	Maximum input voltage PWM frequency: 500 Hz. Push button, potentiometer, 0-10V, DALI, DMX, KNX. Dimming options depend on power supply and additional control units to be separately ordered as accessories
standards	CE



# OKKIO 35 T

## ORDER CODE

### BASE CODE

SS007

### A . POWER SUPPLY

**2** 24V DC  
EXCL. power  
supply

### B . KELVIN

**4** 4000K CRI93  
**5** 3000K CRI93  
**8** 2700K CRI93  
**R** Red


### C . DIFFUSER

**2** spot 15°  
**4** flood 34°  
**5** wide flood 40°

Example: BASE CODE **SS007** A **2** B **5** C **2** D **2** E **A** = **SS007-2522A**

### D . FINISHES

**2** black  
RAL 9005 

**X** custom RAL 

### E . OTHER

**A** IP40  
**C** IP65